

STAND OFF POST MOUNT

TECHNICAL DATA		
MATERIAL	NYLON	NYLON-CF
COLOUR	WHITE / BLACK / RED / GRAY	WHITE / BLACK / RED / GRAY
OPERATING TEMPERATURE	-20 °C to 90 °C	-30 °C to 120 °C
UV RESISTANT	PASS	PASS
CHEMICAL RESISTANT	HIGH	HIGH
FLAME RESISTANT	V - 1 (90 SEC) LSF	V - 0 (60 SEC) LSF
APPLICATION	INDOOR / OUTDOOR	INDOOR / OUTDOOR


* Technical Information subject to change without prior notice. Following UL, IEC Norms
* In house Lab reports can be available upon request.

- Supports cable above or over surface
- Used where limited space is a hindrance


Front View



Side View




Top View



STAND OFF POST MOUNT - VERTICAL							
Part No.	WIDTH [mm]	LENGTH [mm]	HEIGHT [mm]	MAX CABLE BUNCH DIA [mm]	MAX CABLE TIE [mm]	BOLT SIZE [mm]	STATIC LOAD(KG)
ASOPM - V 01	20	30	50	45 x 1 WAY	7.5	5.50	2.50
ASOPM - V 02	20	30	70	30 x 2 WAY	7.5	5.50	3.50
ASOPM - V 03	20	30	115	90 (45 x 2) (30 x 3)	7.5	5.50	4.50



Front View



Side View



Top View



STAND OFF POST MOUNT - HORIZONTAL							
Part No.	WIDTH [mm]	LENGTH [mm]	HEIGHT [mm]	MAX CABLE BUNCH DIA [mm]	MAX CABLE TIE [mm]	BOLT SIZE [mm]	STATIC LOAD(KG)
ASOPM - H 01	4	50	30	45 X 1 WAY	7.5	5.50	2.50
ASOPM - H 02	4	70	30	30 X 2 WAY	7.5	5.50	3.50
ASOPM - H 03	4	115	30	90 (45 X 2) (30 X 3)	7.5	5.50	4.50

* Standard Packing is 100 pcs (Pkt)
* Tolerance : Width + / - 0.50 Thickness + / - 0.20
* Optional Colour, Sizes can be provided upon request