


J CLIP MOUNT - LONG

TECHNICAL DATA		
MATERIAL	NYLON	NYLON-CF
COLOUR	WHITE / BLACK / RED / GRAY	WHITE / BLACK / RED / GRAY
OPERATING TEMPERATURE	-20 °C to 90 °C	-30 °C to 120 °C
UV RESISTANT	PASS	PASS
CHEMICAL RESISTANT	HIGH	HIGH
FLAME RESISTANT	V - 1 (90 SEC) LSF	V - 0 (60 SEC) LSF
APPLICATION	INDOOR / OUTDOOR	INDOOR / OUTDOOR

* Technical Information subject to change without prior notice. Following UL, IEC Norms
* In house Lab reports can be available upon request.

- Quick Snap in and out of cable
- Low profile retain cords, cable or tubing




J CLIP MOUNT - LONG (INDOOR)					
PART NO.	WIDTH (mm)	LENGTH (mm)	HEIGHT (mm)	MAX CABLE BUNCH DIA (mm)	STATIC LOAD (Grams)
AJCML - IN 01	15	9	35	7	270 g
AJCML - IN 02	15	13	35	10	320 g
AJCML - IN 03	15	19	45	16	450 g
AJCML - IN 04	25	24	50	20	520 g

J CLIP MOUNT - LONG (OUTDOOR)					
PART NO.	WIDTH (mm)	LENGTH (mm)	HEIGHT (mm)	MAX CABLE BUNCH DIA (mm)	STATIC LOAD (Grams)
AJCML - OT 01	15	9	35	7	270 g
AJCML - OT 02	15	13	35	10	320 g
AJCML - OT 03	15	19	45	16	450 g
AJCML - OT 04	25	24	50	20	520 g

J CLIP MOUNT - LONG (HEAVY DUTY)						
Part No.	WIDTH (mm)	LENGTH (mm)	HEIGHT (mm)	MAX CABLE BUNCH DIA (mm)	SCREW SIZE (mm)	STATIC LOAD(KG)
AJCML - HD 01	15	9	35	7	2.0	1 KG
AJCML - HD 02	15	13	35	10	3.2	5 KG
AJCML - HD 03	15	19	45	16	5.5	6 KG
AJCML - HD 04	25	24	50	20	5.5	8 KG


* Standard Packing is 100 pcs (Pkt)
* Tolerance Width +/- 0.30 Thickness +/- 0.20
* Optional Colour, Sizes can be provided upon request

Indoor Series




Foam Double Sided Tape

Outdoor Series



Foam Double Sided Heat Resistant-tape

Heavy Series



Drill hole