

2 WAY CABLE TIE BASE MOUNT

TECHNICAL DATA		
MATERIAL	NYLON	NYLON-CF
COLOUR	WHITE / BLACK / RED / GRAY	WHITE / BLACK / RED / GRAY
OPERATING TEMPERATURE	-20 °C to 90 °C	-30 °C to 120 °C
UV RESISTANT	PASS	PASS
CHEMICAL RESISTANT	HIGH	HIGH
FLAME RESISTANT	V - 1 (90 SEC) LSF	V - 0 (60 SEC) LSF
APPLICATION	INDOOR / OUTDOOR	INDOOR / OUTDOOR

* Technical Information subject to change without prior notice. Following UL, IEC Norms
* In house Lab reports can be available upon request.

- Maximum stability for large cable bunch
- Low profile keeps bundle close to mounting surface




2 WAY ADHESIVE MOUNT BASE (INDOOR)						
PART NO.	WIDTH (mm)	LENGTH (mm)	HEIGHT (mm)	MAX CABLE BUNCH DIA (mm)	MAX CABLE TIE (mm)	STATIC LOAD (Grams)
ATWBM - IN 01	14	10	5	20	3	190 g
ATWBM - IN 02	20	12	8	30	6	250 g
ATWBM - IN 03	30	20	9	45	8	370 g
ATWBM - IN 04	40	20	10	60	10	430 g

2 WAY ADHESIVE MOUNT BASE (OUTDOOR)						
Part No.	WIDTH (mm)	LENGTH (mm)	HEIGHT (mm)	MAX CABLE BUNCH DIA (mm)	MAX CABLE TIE (mm)	STATIC LOAD (Grams)
ATWBM - OT 01	14	10	5	20	3	190 g
ATWBM - OT 02	20	12	8	30	6	250 g
ATWBM - OT 03	30	20	9	45	8	370 g
ATWBM - OT 04	40	20	10	60	10	430 g


2 WAY SCREW MOUNT BASE (HEAVY DUTY)							
Part No.	WIDTH (mm)	LENGTH (mm)	HEIGHT (mm)	MAX CABLE BUNCH DIA (mm)	MAX CABLE TIE (mm)	SCREW SIZE (mm)	STATIC LOAD (KG)
ATWBM - HD 01	14	10	5	20	3	2.0	1 KG
ATWBM - HD 02	20	12	8	30	6	3.2	5 KG
ATWBM - HD 03	30	20	9	45	8	5.5	6 KG
ATWBM - HD 04	40	20	10	60	10	5.5	8 KG

* Standard Packing is 100 pcs (Pkt)
* Tolerance Width + / - 0.30 Thickness + / - 0.20
* Optional Colour, Sizes can be provided upon request

Indoor Series



Outdoor Series



Heavy Series

