

BOLT STUD MOUNT

TECHNICAL DATA		
MATERIAL	NYLON	NYLON-CF
COLOUR	WHITE / BLACK / RED / GRAY	WHITE / BLACK / RED / GRAY
OPERATING TEMPERATURE	-20 °C to 90 °C	-30 °C to 120 °C
UV RESISTANT	PASS	PASS
CHEMICAL RESISTANT	HIGH	HIGH
FLAME RESISTANT	V - 1 (90 SEC) LSF	V - 0 (60 SEC) LSF
APPLICATION	INDOOR / OUTDOOR	INDOOR / OUTDOOR


* Technical Information subject to change without prior notice. Following UL, IEC Norms
* In house Lab reports can be available upon request.

- To be used on existing bolts
- Placed between bolt and nut
- Quick and easy maintenance
- Creates an interface to use on existing bolts to fasten cables

Front View



Side View



Top View




Single Way Series



BOLT STUD MOUNT - SINGLE BUNCH							
Part No.	WIDTH [mm]	LENGTH [mm]	HEIGHT [mm]	MAX CABLE BUNCH DIA [mm]	MAX CABLE TIE [mm]	BOLT SIZE [mm]	MAX TORQUE [KN]
ABSM - S 01	20	36	16	24	10	6.0	2.4
ABSM - S 02	24	46	20	32	10	8.0	3.6

Front View



Side View



Top View




Two Way Series



BOLT STUD MOUNT - TWO WAY ADJACENT							
Part No.	WIDTH [mm]	LENGTH [mm]	HEIGHT [mm]	MAX CABLE BUNCH DIA [mm]	MAX CABLE TIE [mm]	BOLT SIZE [mm]	MAX TORQUE [KN]
ABSM - T 01	30	42	22	50 x 2	12	8.00	6.50

Front View



Side View



Top View



Two Way Heavy Series



BOLT STUD MOUNT - TWO WAY HEAVY							
Part No.	WIDTH [mm]	LENGTH [mm]	HEIGHT [mm]	MAX CABLE BUNCH DIA [mm]	MAX CABLE TIE [mm]	BOLT SIZE [mm]	MAX TORQUE [KN]
ABSM - TH 01	25	60	30	55 x 2	12	10.00	7.50


Front View



Side View



Top View



Two Way Ex. Heavy Series



BOLT STUD MOUNT - TWO WAY EXTRA HEAVY							
Part No.	WIDTH [mm]	LENGTH [mm]	HEIGHT [mm]	MAX CABLE BUNCH DIA [mm]	MAX CABLE TIE [mm]	BOLT SIZE [mm]	MAX TORQUE [KN]
ABSM - TEH 01	30	90	26	60 x 2	12	14.00	9.00

* Standard Packing is 100 pcs (Pkt)
* Tolerance - Width +/- 0.30 - Thickness +/- 0.20
* Optional Colour, Sizes can be provided upon request