


4 WAY CABLE TIE BASE MOUNT

TECHNICAL DATA		
MATERIAL	NYLON	NYLON-CF
COLOUR	WHITE / BLACK / RED / GRAY	WHITE / BLACK / RED / GRAY
OPERATING TEMPERATURE	-20 °C to 90 °C	-30 °C to 120 °C
UV RESISTANT	PASS	PASS
CHEMICAL RESISTANT	HIGH	HIGH
FLAME RESISTANT	V - 1 (90 SEC) LSF	V - 0 (60 SEC) LSF
APPLICATION	INDOOR / OUTDOOR	INDOOR / OUTDOOR



* Technical Information subject to change without prior notice. Following UL, IEC Norms
* In house Lab reports can be available upon request.

- Maximum stability for large cable bunch
- Low profile keeps bundle close to mounting surface


Light Series



Heavy Series



Length



Length

4 WAY ADHESIVE MOUNT BASE (INDOOR)						
PART NO.	WIDTH (mm)	LENGTH (mm)	HEIGHT (mm)	MAX CABLE BUNCH DIA (mm)	MAX CABLE TIE (mm)	STATIC LOAD (Grams)
AFWBM - IN 01	20	20	5	20	3	190 g
AFWBM - IN 02	25	25	5	30	6	250 g
AFWBM - IN 03	30	30	7	45	8	370 g
AFWBM - IN 04	40	40	7	60	10	430 g

4 WAY ADHESIVE MOUNT BASE (OUTDOOR)						
Part No.	WIDTH (mm)	LENGTH (mm)	HEIGHT (mm)	MAX CABLE BUNCH DIA (mm)	MAX CABLE TIE (mm)	STATIC LOAD (Grams)
AFWBM - OT 01	20	20	6	20	3	190 g
ATWBM - OT 02	25	25	6	30	6	250 g
ATWBM - OT 03	30	30	8	45	8	370 g
ATWBM - OT 04	40	40	8	60	10	430 g


4 WAY SCREW MOUNT BASE (HEAVY DUTY)							
Part No.	WIDTH (mm)	LENGTH (mm)	HEIGHT (mm)	MAX CABLE BUNCH DIA (mm)	MAX CABLE TIE (mm)	SCREW SIZE (mm)	STATIC LOAD(KG)
AFWBM - HD 01	20	20	6	20	5	2.0	1 KG
AFWBM - HD 02	25	25	6	30	8	3.2	5 KG
AFWBM - HD 03	30	30	8	45	10	5.5	6 KG
AFWBM - HD 04	40	40	8	60	12	5.5	8 KG

* Standard Packing is 100 pcs (Pkt)

* Tolerance Width + / - 0.30 Thickness + / - 0.20


* Optional Colour, Sizes can be provided upon request

Indoor Series




Foam Double Sided Tape

Outdoor Series



Foam Double Sided Heat Resistant Tape

Heavy Series



Conter-Sunk drill hole